

Conventional Electric Concrete VibratorSpecifications

CROMPTON make ISI electric motor 2 HP, 415 volts, 3 Phase AC.

Standard Package

Motor mounted on spring with base frame; alloy steel (Pin type) coupling & attachment, push button D-O-L Starter.

Model no. ADV-PMC-2

Conventional Immersion Vibrator needle (40 mm needle vibrator flexible shaft)Specifications

ADVANCE extra heavy duty 6 meters long flexible shaft immersion vibrators; pin type coupling; with pendulum and rotor.

Needle Diameter 40 mm

Model no. ADV-CFS-40

Conventional Immersion Vibrator needle (50 mm needle vibrator flexible shaft)Specifications

ADVANCE extra heavy duty 6 meters long flexible shaft immersion vibrators; pin type coupling; with pendulum and rotor.

Needle Diameter 50 mm

Model no. ADV-CFS-50

Conventional Immersion Vibrator needle (60 mm needle vibrator flexible shaft)Specifications

ADVANCE extra heavy duty 6 meters long flexible shaft immersion vibrators; pin type coupling; with pendulum and rotor.

Needle Diameter 60 mm

Model no. ADV-CFS-60

ADVANCE IMMERSION TYPE HIGH FREQUENCY CONCRETE VIBRATOR

GREAVES air-cooled petrol engine, complete with base frame, fitted with alloy steel pin type coupling and attachment of ADVANCE make.
